

22KW AC Type 2 EV Charger

INPUT	
Input AC	415Vac (+6% & -10%), 3 Phase, 5 Wire System (3Ph+N+PE)
Input Frequency	50Hz (±3Hz)
OUTPUT	
Output Voltage	400V (±10%)
Output Power	22KW
Output Current	32A per phase
Output Connector	IEC 62196-2, AC Type 2
Protection	Input Over/Under Voltage, Emergency Stop, Over Current, Short Circuit, Over Temperature, Leakage, Lightning Protection
COMMUNICATION	
Interface between Charger and Central Management System (CMS)	GPRS / LAN / Wi-Fi
Communication between EVSE and Central Server	Open Charge Point Protocol (OCPP) v1.6 protocol
DISPLAY	
Display	4.3" TFT Colour Touch Screen for operation interface, Charging Mode Settable
MECHANICAL	
Ingress Protection	IP 54
Cooling	Natural Air Cooling
Mounting	Wall Mount
ENVIRONMENTAL	
Ambient Temperature	0°C to 50°C
Humidity	5% to 95%

*Note: Custom made EV Chargers with different capacities are available
Specifications subject to change without notice*

Regional Offices & Service Centers:

New Delhi | Chandigarh | Patna | Ranchi | Kolkata | Ahmedabad | Jaipur | Lucknow | Guwahati | Bhopal | Raipur
Mumbai | Pune | Nagpur | Bhubaneswar | Hyderabad | Vijayawada | Visakhapatnam | Chennai | Hubli | Cochin
Trivandrum | Calicut | Jammu | Kanpur | Indore | Allahabad | Mysore | Mangalore | Shimoga | Belgaum | Tirupathi
Trichy | Coimbatore | Davanagere | Puducherry | Siliguri | Surat | Nashik | Vadodara
60+ Service Centers Across India in District Level

Head Office & Factory:

Power-One Micro Systems Pvt. Ltd.
GF-3&12, KSSIDC Multistoried Building, 5th Cross, 1st Stage, Peenya Industrial Estate, Bangalore—560058 (INDIA)
Tel: +91-80-22027400, +91-9035010265 | Email: rajeshmr@poweroneups.com | Website: www.poweroneups.com

